7147LSEC SECURITY



Brand: Avital
Product Code: 7147LSEC
Stock: 6
UPC: 044476161650
FCC ID: EZSDEI7146
MPN: Avital 7147LSEC
Location: Cleveland, Ohio

Price: $54.99

Short Description
Avital 1-Way Security Remote

Genuine Avital 7147LSEC 1-Way 4-Button Security Remote Control — FCC ID: EZSDEI7146. Features an **asterisk button instead of the remote-start icon**. Designed for and supplied with Avital 2103L, 3103L, 3103LX and 3308LS systems; also works with the compatible older Avital systems listed in the full description. **One brand-new 7147LSEC remote with two CR2016 batteries included. $54.99.** Programming required.

Description

Avital 7147LSEC Security 1-Way 4-Button Remote Control

Replace a lost, damaged or nonworking transmitter with a **brand-new, genuine Avital 7147LSEC 1-Way 4-Button remote control**. This original Directed Electronics transmitter is designed for compatible Avital vehicle security, keyless-entry and remote-start systems.

The Avital 7147LSEC provides convenient wireless control of supported vehicle functions, including locking, unlocking and auxiliary operations, depending on the installed system and configuration.

This listing includes **one genuine Avital 7147LSEC remote control**. Two CR2016 batteries are included with the remote. **Programming is required.**

The **Avital 7147LSEC security remote** is designed for and supplied with the newer **2103L, 3103L, 3103LX and 3308LS** systems. It also works with the compatible older Avital systems listed below.

This security version has an **asterisk on the button instead of the remote-start icon**.

$54.99 GENUINE AVITAL 7147LSEC

Brand-New 1-Way 4-Button Remote Control

Two CR2016 Batteries Included

GENUINE AVITAL Original Directed Electronics transmitter

1-WAY REMOTE Four-button transmitter design

SECURITY VERSION Asterisk button marking

BRAND NEW Two CR2016 batteries included

Avital 7147LSEC Replacement Remote Compatibility

The Avital 7147LSEC replaces the 7143L and the previous-generation Avital transmitters listed below when the installed system and receiver support the same transmitter technology. The 7147LSEC uses the same remote-control platform as the 7147L and 7147LS, with an asterisk button marking for security applications.

AVITAL 7143L Previous-Generation Remote
Replaced by 7147LSEC on Compatible Systems

AVITAL 7147LSEC Original Remote
Actual Model Supplied

AVITAL 474L Earlier-Generation Remote
Verify Receiver Compatibility

AVITAL 473L Earlier-Generation Remote
Verify Receiver Compatibility

AVITAL 476L Earlier-Generation Remote
Verify Receiver Compatibility

AVITAL 477L Earlier-Generation Remote
Verify Receiver Compatibility

AVITAL 7133L Earlier-Generation Remote
Verify Receiver Compatibility

What you receive: One genuine Avital 7147LSEC remote control. The other model numbers above are compatibility references only and are not included. Interchangeability must be confirmed against the installed system and receiver.

Genuine Avital Remote Control

The Avital 7147LSEC is an original **Directed Electronics 1-Way transmitter**, not a generic reproduction or refurbished remote. It is intended for compatible Avital systems requiring this generation of remote-control technology.

Its four-button design provides convenient access to the functions supported by the installed system. The exact operation of each button depends on the vehicle's security or remote-start configuration.

When replacing a previous-generation remote, confirming the original transmitter model and installed receiver is especially important. We recommend verifying the replacement compatibility and system information before purchasing.

Avital 7147LSEC Product Specifications

CR2016 × 2	Battery Type per Remote
1	Remote Quantity
INCLUDED	Two CR2016 batteries included
7147LSEC	Remote Model / MPN
EZSDEI7146	FCC ID
AVITAL	Brand
1-WAY	Remote Type
4 BUTTONS	Transmitter Design
ORIGINAL	Genuine Manufacturer Remote

BRAND NEW Product Condition

REQUIRED Vehicle Programming

Avital 7147LSEC System Compatibility

The Avital 7147LSEC is intended for newer systems listed above and select compatible older Avital vehicle security, keyless-entry and remote-start systems. Compatibility depends on the installed control module, antenna and receiver.

NEWER AVITAL SECURITY & KEYLESS-ENTRY SYSTEMS

- 2103L
- 3103L
- 3103LX
- 3308LS

AVITAL SECURITY SYSTEMS

- 3100L
- 3300L
- 3305L

AVITAL REMOTE START SYSTEMS

- 2101L
- 4103L

- 4105L
- 4108L
- 4308L

AVITAL SECURITY & REMOTE START

- 5303L
- 5305L
- Other supported original-generation installations

System Model Reference: The models above are reference applications associated with this generation of Avital equipment. Confirm the installed receiver and original transmitter before ordering. A system model alone does not guarantee compatibility across every revision.

Original Remote Identification: Check the model number and FCC ID printed on your existing remote control. Matching the original transmitter is the most reliable starting point.

Receiver Compatibility: Different generations of Avital equipment may use different transmitter technology. The installed antenna and receiver determine whether the 7147LSEC can be learned.

Programming Required: The Avital 7147LSEC must be programmed to a compatible, functioning system before use. Refer to the separate **Programming Instructions** tab.

Replacing an Earlier-Generation Avital Remote

Avital has offered several generations of remote controls for vehicle security and remote-start systems. Some earlier-generation transmitters share compatible receiver technology, but matching the Avital brand alone does not establish interchangeability.

When replacing an original remote, identify the model number on the back of the transmitter, check its FCC ID and verify the installed system's receiver. This helps ensure that the replacement can be successfully programmed.

Access 1 Alarm & Audio offers the **actual original Avital 7147LSEC** as a replacement for the 7143L and compatible previous-generation transmitters.

7147LSEC Security Version — Asterisk Button

This listing supplies **one genuine Avital 7147LSEC security remote with the asterisk button**. The 7147LS also uses an asterisk marking, while the 7147L uses a remote-start icon.

The button marking identifies the version. Available functions depend on the installed system and configuration; a remote does not add remote-start capability to a security-only system.

Prefer the version with the remote-start icon? Order the Avital 7147L here.

{ "@context": "https://schema.org", "@type": "Product", "@id": "https://www.access1ala

rm.com/car-alarms-and-remote-start/remote-controls/avital/7147l/7147lsec-security#product", "name": "Avital 7147LSEC Security 1-Way 4-Button Remote Control", "description": "Genuine Avital 7147LSEC security remote with asterisk button, $54.99. For 2103L, 3103L, 3103LX, 3308LS and compatible older systems. Batteries included.", "image": ["https://www.access1alarm.com/images/com_eshop/products/7147LSEC.jpg"], "url": "https://www.access1alarm.com/car-alarms-and-remote-start/remote-controls/avital/7147l/7147lsec-security", "mpn": "7147LSEC", "brand": { "name": "Avital", "@type": "Brand" }, "manufacturer": { "name": "Directed Electronics", "@type": "Organization" }, "category": "Automotive Security and Remote Start Replacement Remote Controls", "additionalProperty": [{ "@type": "PropertyValue", "name": "Included Remote Quantity", "value": 1 }, { "@type": "PropertyValue", "name": "FCC ID", "value": "EZSDEI7146" }, { "@type": "PropertyValue", "name": "Batteries", "value": "Two CR2016 batteries included" }, { "@type": "PropertyValue", "name": "Remote Type", "value": "1-Way 4-Button" }, { "@type": "PropertyValue", "name": "Replacement Remote References", "value": "7143L, 473L, 474L, 476L, 477L, 7133L; verify system and receiver compatibility" }, { "@type": "PropertyValue", "name": "Programming", "value": "Required for all included remotes" }, { "@type": "PropertyValue", "name": "Button Marking", "value": "Asterisk (security version)" }, { "@type": "PropertyValue", "name": "Newer System Models", "value": "2103L, 3103L, 3103LX, 3308LS" }, { "@type": "PropertyValue", "name": "Older Compatible System References", "value": "2101L, 3100L, 3300L, 3305L, 4103L, 4105L, 4108L, 4308L, 5303L, 5305L; verify installed system and receiver" }], "offers": { "seller": { "url": "https://www.access1alarm.com/", "@type": "Organization", "name": "Access 1 Alarm & Audio" }, "priceCurrency": "USD", "itemCondition": "https://schema.org/NewCondition", "url": "https://www.access1alarm.com/car-alarms-and-remote-start/remote-controls/avital/7147l/7147lsec-security", "price": "54.99", "@type": "Offer" } }

Programming Instructions

Avital 7143L Programming Instructions

Original 1-Way 4-Button Remote Control - Directed Electronics Learn Routine

Follow these instructions to program your **Avital 7143L remote control** to a compatible earlier-generation Avital security, keyless-entry or remote-start system.

Before beginning, locate the vehicle's **Valet/Programming Switch**. Earlier systems generally use a separate push-button installed beneath the dashboard. Some compatible systems use a programming button integrated into the windshield-mounted antenna or Control Center.

BEFORE YOU BEGIN

Make sure the security system is **disarmed** and the status LED has been **OFF for at least 60 seconds**.

On some older installations, the separate Valet/Programming Switch connects to the control module's **BLUE two-pin port** using a gray wire and a black wire with a gray stripe.

Have all remotes you intend to use available. Some systems require each transmitter to be programmed during the same learning session.

For compatible earlier-generation Avital remote-start systems using a separate Valet/Programming Switch.

1. **DOOR:** Open the driver's door and leave it open.
2. **KEY:** Turn the ignition key to the **ON** position. Do not start the engine.
3. **CHOOSE:** Within **10 seconds**, press and release the **Valet/Programming Switch once**.
4. **HOLD:** Press the Valet/Programming Switch **one more time and continue holding it**. Wait for the status LED to flash and the siren or horn to sound, if connected. **Do not release the switch.**
5. **TRANSMIT:** While continuing to hold the switch, press the **LOCK** button on the **Avital 7143L remote**. The system may chirp or flash to confirm that the remote was learned.
6. **ADDITIONAL REMOTES:** If your system supports learning additional remotes during the same session, repeat the transmitter step for each compatible remote.
7. **RELEASE:** Release the Valet/Programming Switch, turn the ignition **OFF**, and wait approximately **60 seconds**.

For compatible earlier-generation Avital security-only or keyless-entry systems using a separate Valet/Programming Switch.

1. **DOOR:** Open the driver's door and leave it open.
2. **KEY:** Turn the ignition key to the **ON** position.
3. **CHOOSE:** Within **10 seconds**, press and release the **Valet/Programming Switch seven times**.
4. **HOLD:** On the **eighth press**, continue holding the Valet/Programming Switch. **Do not release it.**
5. **CONFIRM:** Wait for the status LED to flash and the siren or horn to sound, if connected. Continue holding the switch.
6. **TRANSMIT:** Press the **LOCK** button on the **Avital 7143L remote**. Wait for the system's confirmation, if available.
7. **ADDITIONAL REMOTES:** If supported, program additional compatible remotes before leaving programming mode.
8. **RELEASE:** Release the Valet/Programming Switch, turn the ignition **OFF**, and wait approximately **60 seconds**.

For compatible Avital remote-start systems equipped with a windshield-mounted **Control Center** containing an integrated programming button and status LED.

1. **DOOR:** Open the driver's door and leave it open.
2. **KEY:** Turn the ignition key to the **ON** position.
3. **CHOOSE:** Within **10 seconds**, press and release the windshield-mounted programming button **once**.
4. **HOLD:** Press the programming button **one more time and continue holding it**. Wait for the LED to flash and the siren or horn to sound, if connected.
5. **TRANSMIT:** While continuing to hold the button, press the **LOCK** button on the **Avital 7143L remote**.
6. **ADDITIONAL REMOTES:** Program additional compatible remotes during the same session, if supported.
7. **RELEASE:** Release the programming button, turn the ignition **OFF**, and wait approximately **60**

seconds.

For compatible Avital security or keyless-entry systems equipped with a windshield-mounted Control Center and integrated programming button.

1. **DOOR:** Open the driver's door and leave it open.
2. **KEY:** Turn the ignition key to the **ON** position.
3. **CHOOSE:** Within **10 seconds**, press and release the windshield-mounted programming button **seven times**.
4. **HOLD:** On the **eighth press**, continue holding the programming button. **Do not release it.**
5. **CONFIRM:** Wait for the status LED to flash and the siren or horn to sound, if connected.
6. **TRANSMIT:** While holding the programming button, press the **LOCK** button on the **Avital 7143L remote**.
7. **ADDITIONAL REMOTES:** Program any additional compatible remotes during the same session, if supported.
8. **RELEASE:** Release the programming button, turn the ignition **OFF**, and wait approximately **60 seconds**.

SEPARATE VALET/PROGRAM SWITCH: Usually mounted beneath the dashboard on earlier-generation systems.

WINDSHIELD CONTROL CENTER: Combines the status LED and programming button in one windshield-mounted assembly.

REMOTE-START SYSTEMS: The procedures above use one press-and-release followed by another press-and-hold.

SECURITY-ONLY SYSTEMS: The procedures above use seven press-and-release operations followed by

holding the eighth press.

PROGRAMMING CONFIRMATION: Depending on the installed system, a siren chirp, horn sound or LED flash may confirm successful enrollment.

IMPORTANT PROGRAMMING INFORMATION

The Avital 7143L must be programmed to a **compatible receiver and control module**. Matching the brand name alone does not guarantee compatibility.

Programming sequences may vary by system generation and installed configuration. If your system does not respond as described, consult the installation or owner's manual for your specific Avital control module.

After programming, turn the ignition OFF, allow the system to exit programming mode, and test the supported remote functions.

Specification

Remote Control	
Works With Antenna(s)	544N, 548T, 6102T, 6112T, 6166T, 6213T, A6133T, A6167T
Battery Type	CR2016 (X2)
FCC ID	EZSDEI7146
IC Number	1513A-7146
Frequency	434Mhz
Range	1/4-Mile
1-Way or 2-Way	1-Way